
OCEAN · ŞERİT LED KONNEKTÖRLERİ

Mini Kristal Şerit LED Konnektörü, DC / Dişi Soket Kablolu

LED Strip Connector — SMD Mini crystal with wire to DC / DuPont

ÜRÜN KODU · PRODUCT CODE

DNZ-SLK-17



UYGUN ŞERİT GENİŞLİĞİ · STRIP WIDTH
5 mm, 8 mm, 10 mm

PİN SAYISI · PINS
2P, 3P, 4P, 5P

NOMİNAL GERİLİM / AKIM · RATING
DC 36 V / 5 A

KABLO · CABLE
24–22 AWG, Ø1.5–Ø1.6 mm

ÇALIŞMA SICAKLIĞI · OPERATING TEMP.
-10 °C ~ +45 °C

SERİ · SERIES
Mini Kristal Seri

TEKNİK ÖZELLİKLER SPECIFICATIONS

Seri Series	**Mini Kristal Seri**
Bağlantı Şekli Connection	**Kapaklı kristal klips (lehimsiz)**
Kablo Cable	**24–22 AWG, Ø1.5–Ø1.6 mm**
Çalışma Sıcaklığı Operating temp.	**-10 °C ~ +45 °C**
Nominal Gerilim / Akım Rating	**DC 36 V / 5 A**
Uygun Şerit Genişliği Strip width	**5 mm, 8 mm, 10 mm**
Pin Sayısı Pins	**2P, 3P, 4P, 5P**

MODELLER VERSIONS

KOD	MODEL
DNZ-OA2P-5-DC	OA2P-5-DC (COB/SMD-5mm tek renk)
DNZ-OA2P-8-DC	OA2P-8-DC (COB/SMD-8mm tek renk)
DNZ-CA3P-8-MK	CA3P-8-MK (SMD-8mm-3P)
DNZ-CA4P-8-MK	CA4P-8-MK (SMD-8mm-4P)
DNZ-CA2P-10-DC	CA2P-10-DC (SMD-10mm-2P)
DNZ-CA3P-10-MK	CA3P-10-MK (SMD-10mm-3P)
DNZ-CA4P-10-MK	CA4P-10-MK (SMD-10mm-4P)
DNZ-CA5P-10-MK	CA5P-10-MK (SMD-10mm-5P)
DNZ-OA3P-8-MK	OA3P-8-MK (COB-8mm çift renk (CCT))
DNZ-OA4P-8-MK	OA4P-8-MK (COB-8mm RGB)
DNZ-OA2P-10-DC	OA2P-10-DC (COB-10mm tek renk)
DNZ-OA3P-10-MK	OA3P-10-MK (COB-10mm çift renk (CCT))
DNZ-OA4P-10-MK	OA4P-10-MK (COB-10mm RGB)

Teknik değerler nominaldir, ±%10 tolerans gösterebilir. Ürün geliştirme nedeniyle özellikler önceden haber verilmeksizin değiştirilebilir. · All values are nominal (±10%). Specifications subject to change without notice.

Deniz Medya Reklam Elektrik İnşaat Ltd. Şti.
Ankara Merkez: 100. Yıl Bulvarı No:94, Ostim / Yenimahalle / Ankara
İstanbul Şube: Abdurrahmangazi Mah. Atayolu Cad. No:63/B, Sancaktepe / İstanbul

denizled.com
satis@denizled.com
0312 543 76 74 · 0216 515 45 06